

ValProbe[®] RT 1.3

SOFTWARE UPDATE BRINGS IN NUMEROUS KEY FEATURES



ValProbe RT, Kaye's industry leading wireless validation system, is ready to operate at version 1.3. This major software update implements many new features that greatly improve user experience. ValProbe RT 1.3 is available as a free download from Kaye's website. One of the major features of this update is its capacity to support up to 50 ValProbe RT Loggers in one study. A highly requested item, Kaye is excited to add this to the ValProbe RT software.

ValProbe RT 1.3 supports User Management with ACTIVE DIRECTORY*. ValProbe RT 1.3 introduces support for

starting qualification studies also by a temperature condition and the flexibility to replace the relative humidity sensor or CO₂ sensor of your RT Data Logger in the field. Additionally, the update enables you to display and save mapping information for real-time-off studies, streamlining data analysis and record-keeping. These enhancements will make your temperature, pressure and humidity monitoring even more convenient. With the newly introduced volume-adjustable buzzer function user comfort is improved. An optimized battery status function and the new automatic saving after completing a validation study enhance user


comfort, particularly in long-term measurements. Combined with the Kaye Common Reporting Tool 1.4, up to 3 validation studies can be merged into one report. An additional standard evaluation tool based on AFNOR FDX15-140 further simplifies the validation of climatic chambers, cooling systems, and incubators. Another feature is the display of the internal Logger temperature and the mode of the base station. Moreover, the upgrade enables a Logger-based search for individual verification reports, including the history of Logger usage.

The latest extension of the Kaye ValProbe RT product line introduces interesting technical and user-oriented features. Other improvements to the user interface and the integration of new, additional evaluation functions enhance user-friendliness.


FEATURES:

- Support of up to 50 Logger in one validation study
- Qualification studies start based on temperature

- Further optimized battery estimation function
- Individual verification report for each single Logger and merge to one verification report
- Common Reporting Tool enables to merge up to 3 individual studies into one single report
- Standard Report according AFNOR FDX15-140 requirements
- Display base Station Mode; Added Base Station mode in Discovery screen for each base station tile
- Search verification report based on individual Logger
- Easy mapping and reuse – the update enables you to display and save mapping information for real-time-off studies
- Auto-Save-Function
- Volume adjustable Buzzer at base station
- Support of CO₂ & RH sensor replacement in the field (Field replaceable sensors)
- Support of the newly introduced ValProbe RT CO₂ Logger
- Displaying internal Logger battery temperature improves security



RT OFF Study Feature



Logger Verification History

Kaye representative contact:

EUROPE, MIDDLE EAST, AFRICA AND ASIA
 Amphenol Advanced Sensors Germany GmbH
 Sinzheimer Strasse 6
 D-75179 Pforzheim
 T: +49 (0) 7231-14 335 0
 F: +49 (0) 7231-14335 29
 Email: kaye@amphenol-sensors.com

USA/AMERICAS
 Amphenol Thermometrics, Inc.
 967 Windfall Road
 St. Marys, PA 15857
 T: +1(814) 834-9140
 F: +1(814) 781-7969
 Email: kaye-us@amphenol-sensors.com

Request a demo:

INDIA
 Amphenol Interconnect India Pvt Ltd.
 Plot no. 6, Survey No.64 | Software Units layout
 MAHAVEER TECHNO PARK
 Hitech City, Madhapur | Hyderabad,
 Telangana – 500081 | T: +91 40 33147100
 Email: kaye-india@amphenol-sensors.com

CHINA
 Amphenol (Changzhou) Connector
 Systems Co., Ltd. Building 10,
 Jintong Industrial Park, No. 8 Xihu Road,
 Wujin High-Tech Development Zone,
 Changzhou, Jiangsu 213164
 T: 0086-519-83055197



Warranty and disclaimer: The information mentioned on documents are based on our current tests, knowledge and experience. Because of the effect of possible influences in an application of the product, they do not exempt the user from their own tests, checks and trials. A guarantee of certain properties or a guarantee for the proper suitability of the product for a specific, especially permanent application can not be derived from our data. Liability is therefore excluded to that extent permitted by law. Any proprietary rights of third parties as well as existing laws and regulations must be observed by the recipient of the product on his own responsibility.

© 2024 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.